

Abstract Submitted  
for the MAR07 Meeting of  
The American Physical Society

**Charge injection and transport in fluorene-based copolymers.<sup>1</sup>**

HON HANG FONG, GEORGE G. MALLIARAS, Cornell University, TIANJIAN LU, DAVID DUNLAP, University of New Mexico — Fluorene-based copolymer is considered to be one of the most promising hole transporting and blue light-emitting conjugated polymers used in polymeric light-emitting diodes (PLEDs). Time-of-flight (TOF) technique has been employed to evaluate the charge drift mobility under a temperature range between 200 - 400 K at the thick film regime (1-10 micron). Meanwhile, contact ohmicity is studied by Dark Current Space Charge Limited Conduction (DISCLC) technique. Charge injection efficiencies from different electrical contacts are also studied and the corresponding injection barriers are independently investigated by photoemission and electroabsorption spectroscopies. Results show that the copolymers exhibit non-dispersive charge transport behavior and possess superior mobilities of up to  $0.01\text{cm}^2\text{V}^{-1}\text{s}^{-1}$  while single-carrier devices from various electrical contacts such as PEDOT:PSS are varied, depending on the chemical structure of amine component in the fluorene-triarylamine copolymers. Results will shed light on the enhancement of device efficiency and stability in the future polymer electronic devices.

<sup>1</sup>H.H.F. would like to acknowledge the postdoctoral fellowship funded by the Croucher Foundation in Hong Kong

Hon Hang Fong  
Cornell University

Date submitted: 03 Dec 2006

Electronic form version 1.4