

Abstract Submitted
for the MAR08 Meeting of
The American Physical Society

Turbulent Viscosity Coefficient in 3-Dimensional Turbulence HIROSHI SHIBATA, Sojo University — A new model for the large-eddy simulation (LES) is proposed. The LES has been accepted as the standard formalism for calculating observables concerning turbulence. In the application of the LES, several models are chosen. The purpose of the present paper is for us to propose one of the most physical models. The LES is usually written down as

$$\frac{\partial U_i}{\partial t} + (\vec{U} \cdot \vec{\nabla})U_i = -\frac{1}{\rho} \frac{\partial P}{\partial x_i} + \nu_0 \Delta U_i - \frac{\partial Q_{ij}}{\partial x_j}. \quad (1)$$

The above equation is rewritten as

$$\frac{\partial U_i}{\partial t} + (\vec{U} \cdot \vec{\nabla})U_i = -\frac{1}{\rho} \frac{\partial P}{\partial x_i} + \nu \Delta U_i \quad (2)$$

and ν is referred to as turbulent viscosity coefficient. The statistical mechanical method by Helfand[1] is extended replacing the relationship between the thermal velocity and the kinetic viscosity coefficient by the one between the turbulent velocity and the turbulent viscosity coefficient[2]. The major assumption here is the Gaussian statistics for the turbulent velocity. The concrete calculation using the lattice Boltzmann method is shown for 3-dimensional turbulence. [1] E. Helfand, Phys. Rev. 119,1(1960). [2] H. Shibata, J. Phys. Soc. Jpn. 76,024002(2007).

Hiroshi Shibata
Sojo University

Date submitted: 05 Oct 2007

Electronic form version 1.4