

Abstract Submitted
for the MAR08 Meeting of
The American Physical Society

Phase behavior of polyelectrolyte multilayer investigated by thin film calorimetry H. HUTH, University Rostock, Institute of Physics, Uniplatz 3, 18051 Rostock, Germany, R. MUELLER, MPI fuer Kolloid- und Grenzflaechenforschung, Am Muehlenberg, 14424 Potsdam, A. FERY, University Bayreuth Physical chemistry II, Universitaetsstr. 30, 95447 Bayreuth, C. SCHICK — Polyelectrolyte multilayer can be easily assembled using spraying or dipping of the different polyelectrolytes [1]. The thickness of the produced layers (nanometer range) is well controlled by the preparation conditions. Only a few methods are available for dynamic investigations, as afm for mechanical properties [2]. AC-chip calorimetry is used as a very sensitive tool for calorimetric investigations of such thin films as demonstrated for thin polymeric films [3]. To investigate the phase behavior of polyelectrolytes the humidity is used as a new parameter in addition to temperature for calorimetry. First measurements with the modified calorimeter for the PSS/PDADMAC polyelectrolyte multilayer system are shown. Further extensions of the calorimeter for better understanding of the phase behavior are discussed. [1] Decher, G. and J.D. Hong, Phys. Chem. Chem. Phys., 1991. 95(11): 1430. [2] Mueller, R., et al. Macromolecules, 2005. 38(23): 9766. [3] Huth, H., Minakov, A. A., Schick, C., J. Polym. Sci. B Polym. Phys. 2006 44: 2996.

Heiko Huth
University Rostock, Institute of Physics, Uniplatz 3, 18051 Rostock, Germany

Date submitted: 27 Nov 2007

Electronic form version 1.4