

Abstract Submitted  
for the MAR08 Meeting of  
The American Physical Society

**Measurements of a dc-SQUID phase qubit using rf-reflectometry<sup>1</sup>**

R.M. LEWIS, University of Maryland, B.K. COOPER, S.K. DUTTA, T. A. PALOMAKI, HANHEE PAIK, A. PRZYBYSZ, H. KWON, J. R. ANDERSON, C. J. LOBB, F. C. WELLSTOOD — We performed measurements of a *Nb/AlOx/Nb* dc-SQUID phase qubit at 100 mK by monitoring the plasma frequency,  $f_p$ , of the readout/isolation junction. This qubit contains two Josephson junctions (JJ) separated by a 1.3 nH inductance; one JJ operates as a pure phase qubit, the second JJ isolates and reads out the qubit junction. When driving the isolation junction at 1.5 GHz, near  $f_p$ , current fluctuations in the SQUID loop cause fluctuations in  $f_p$  which appear in the sidebands of the reflected microwave power. At 100 mK we find an effective flux noise,  $S_{\Phi}^{0.5}$  of  $50 \mu\Phi_0/Hz^{0.5}$  at 1 Hz. The measurement bandwidth is about 10 MHz, the upper limit being set by the  $Q$  of the readout junction. We will discuss how the measurement performance depends on biasing parameters of each junction.

<sup>1</sup>Funding from the Joint Quantum Institute and the NSA.

Rupert Lewis  
University of Maryland

Date submitted: 27 Nov 2007

Electronic form version 1.4