

Abstract Submitted  
for the MAR08 Meeting of  
The American Physical Society

**Single-crystalline rutile TiO<sub>2</sub> nanowires by mass selected Ni catalyst: Synthesis and electrical properties** MYUNG HWA KIM, CHRISTOPHER LARSON, JEONG MIN BACK, XIHONG CHEN, MARTIN MOSKOVITS, ALEC WODTKE, Department of Chemistry & Biochemistry, University of California at Santa Barbara — We present a novel method for growing high quality TiO<sub>2</sub> nanowires using mass-selected Ni clusters of nanometer sizes produced by magnetron sputtering and also show their electric field-effect functions. Single-crystalline TiO<sub>2</sub> nanowires(NWs) are grown by atmospheric pressure physical vapour deposition(APPVD) process, using TiO and Ti metal powders as a Ti source and Ni nanoparticles as a catalyst, respectively. For the TiO<sub>2</sub> NWs growth, first, the Ti metal layer with a thickness of ~50nm was then deposited on the SiO<sub>2</sub>/Si substrate by the e-beam evaporation technique and subsequently, the mass selected Ni clusters by using magnetron sputtering source combined with a quadrupole mass filter was deposited onto the Ti layer. APPVD growth was then performed in a horizontal quartz tube furnace at 800°C-950°C by introducing high purity Ar carrier gas (99.999%) with the flow rate of 300 sccm for 2 hours. The  $I - V$  curves are linear over the entire annealing temperature range at 200 ~500°C, showing that the electrodes form good ohmic contacts with the nanowires. The  $I$  vs  $V_G$  curves for various values of  $V_{SD}$  and gate dependent  $I - V$  curves of a TiO<sub>2</sub> nanowire configured as a back-gated FET are also obtained and will be discussed.

Myung Hwa Kim  
Dept of Chemistry & Biochemistry, University of California at Santa Barbara

Date submitted: 28 Dec 2007

Electronic form version 1.4