

Abstract Submitted
for the MAR11 Meeting of
The American Physical Society

Heat transfer through a dual-walled carbon nanotube¹ KHOA BUI, The University of Oklahoma, CEDRIC COUSIN, Blaise Pascal University, Clermont-Ferrand, HUONG NGUYEN, The University of Oklahoma, ALBERTO STRIOLO, DIMITRIOS PAPAVALASSILIOU, The University of Oklahoma — Molecular Dynamics simulations are used to investigate the resistance to heat transfer between the walls of dual-walled carbon nanotubes (DWCNTs). Recent computational results have indicated that the carbon nanotube to carbon nanotube thermal boundary resistance (TBR) can be as high or higher than the TBR between a nanotube and the surrounding matrix (e.g., epoxy or octane) in the case of composites. This generates the question of whether heat transfer in multi-walled carbon nanotubes occurs through the outer nanotube only or not. We discuss here results for a DWCNT composed of a (5,5) nanotube inside a (10,10) nanotube, as well as the differences between this case and the case of a (6,6) inside a (19,0).

¹DOE ER64239 0012293, DOD FA9550-10-1-0031

Dimitrios Papavassiliou
The University of Oklahoma

Date submitted: 21 Nov 2010

Electronic form version 1.4