

Abstract Submitted
for the MAR14 Meeting of
The American Physical Society

High-speed velocimetry inside imploding cylindrical liners¹

DANIEL DOLAN, RAY LEMKE, DEVON DALTON, ERIC HARDING, RYAN MCBRIDE, MATTHEW MARTIN, Sandia National Laboratories, BRENT BLUE, General Atomics, SCOTT WALKER, National Security Technologies — Dynamic planar compression is conceptually simple but difficult to maintain at extreme pressure (>5 Mbar). Higher pressures are attainable with imploding cylindrical liners, using Photonic Doppler velocimetry (PDV) to track the liner interior. PDV measures Doppler shift directly—1 GHz of beat frequency for every 1 km/s of velocity—requiring a special “leapfrog” approach for liners traveling in excess of 20 km/s. Single-point and multi-point PDV measurements have been performed in aluminum, beryllium, and tantalum liners under ramp compression, and the technique can readily applied to other implosion experiments. Combined with electrical current diagnostics, these measurements test thermodynamic equations of state at pressures up to 10 MBar and beyond.

¹Sandia National Laboratories is a multi-program laboratory operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy’s National Nuclear Security Administration under contract DE-AC04-94AL85

Daniel Dolan
Sandia National Laboratories

Date submitted: 12 Nov 2013

Electronic form version 1.4