

Abstract Submitted  
for the MAR16 Meeting of  
The American Physical Society

**Modified Graphene Oxide for Long Cycle Sodium-Ion Batteries<sup>1</sup>**

MUHAMED SHAREEF, Kansas State University, HARRISON GUNN, Syracuse University, VICTORIA VOIGT, GURPREET SINGH, Kansas State University — Hummer's process was modified to produce gram levels of 2-dimensional nanosheets of graphene oxide (GO) with varying degree of exfoliation and chemical functionalization. This was achieved by varying the weight ratios and reaction times of oxidizing agents used in the process. Based on Raman and Fourier transform infrared spectroscopy we show that potassium permanganate ( $\text{KMnO}_4$ ) is the key oxidizing agent while sodium nitrate ( $\text{NaNO}_3$ ) and sulfuric acid ( $\text{H}_2\text{SO}_4$ ) play minor role during the exfoliation of graphite. Tested as working electrode in sodium-ion half-cell, the GO nanosheets produced using this optimized approach showed high rate capability and exceptionally high energy density of  $\sim 500$  mAh/g for up to at least 100 cycles, which is among the highest reported for sodium/graphite electrodes. The average Coulombic efficiency was approximately 99 %.

<sup>1</sup>NSF Grant No. 1454151

Muhamed Shareef  
Kansas State University

Date submitted: 06 Nov 2015

Electronic form version 1.4