

Abstract Submitted
for the MAR08 Meeting of
The American Physical Society

Nano-scale TiB₂ Precipitates in MgB₂ Superconducting Wire¹

D.K. FINNEMORE, M.E. TILLMAN, P.C. CANFIELD, S.L. BUD'KO, Y.Q. WU, M.J. KRAMER, Ames Lab / Iowa State University, J.V. MARZIK, Specialty Materials, Inc., Lowell, MA, M. RINDFLEISCH, Hyper Tech Research Inc., Columbus, OH, S.T. HANNAHS, NHMFL, Tallahassee, FL — Superconducting MgB₂ wire containing uniformly dispersed, nano-scale TiB₂ precipitates has been produced using a plasma synthesis method to make the starting Ti doped B powder. A powder-in-tube method is used for making the wire. Sub-micrometer size MgB₂ grains are decorated with a random dispersal of 5 to 20 nm precipitates. The superconducting properties are reported for a family of powder-in-tube wires fabricated with pure boron, carbon doped boron, and titanium doped boron. The particle size of the doped boron powder, of 50 to 100 nm, permits low reaction temperatures and short reaction times. The best reaction temperatures are in the neighborhood of 700 C for reaction times of approximately 20 min. For the Ti doped, PIT wire, at T = 20 K, J_c crosses 10,000 A/cm² at 1.8 T.

¹Work at the Ames Laboratory was supported by the Department of Energy, Basic Energy Sciences under Contract No. DE-AC02-07CH11358.

P.C. Canfield

Date submitted: 29 Nov 2007

Electronic form version 1.4